

Flaggstång

	6,6 m	8 m	9 m	10 m	12 m		
Vikt, flaggstång (kg)	23	26	28	35	40		
Topp diameter (mm)	72	65	65	65	65		
Botten diameter (mm)	107	120	128	135	148		
Godstjocklek, flaggstång (mm)	Ca 3,0	Ca 3,0	Ca 3,0	Ca 3,5	Ca 3,5		

Tillbehör

Toppkula, plexiglas & plast (mm)	135	135	135	135	135		
Toppkula, metall guld/silver (mm)	120	120	120	150	150		
A Höjd till knap & låsbar lucka (mm)	1400	1400	1400	1400	1400		
B Avstånd till vev, alt 1 (mm)	900	900	900	900	900		
C Avstånd till vev, alt 2 (mm)	550	550	550	550	550		
D Armerad utvändig flagglina (ø mm)	5,0	5,0	5,0	5,0	5,0		
D Draghållfasthet, flagglina 5 mm (kg)	600	600	600	600	600		
D Längd på flagglina 5 mm (m)	16	16	16	23	23		
E Knap längd (mm)	165	165	165	165	165		
E Fästhål Knap, CC mått (mm)	33,5	33,5	33,5	33,5	33,5		

Teknisk info

Flaggstångsfotens form		△	△	△	△	△		
G Fotens hål, 3 x CC mått (mm)	168	168	168	168	168			
H Fotens hål, 4 x CC mått (mm)	-	-	-	-	-			
I Hålens ovala dimension (mm)	22x35	22x35	22x35	22x35	22x35			
F Stålrörets längd (mm)	450	600	600	600	600			
F Stålrörets godstjocklek (mm)	2,5	3,0	3,0	4,0	4,0			
F Ytterdiameter, Stålrör (mm)	75	102	102	121	121			

